

CHAIN SHACKLE WITH OVERSIZE SCREW PIN

316-NM STAINLESS STEEL



Import



Drop Forged




Load Rated



Suncor Exclusive



MIL-SPEC



ITEM	A (size)	B	C	D	X (height)	Y (length)	Z (width)	WLL (lb)	WT (lb)	PACKAGING TYPE	EACH (qty)	INNER (qty)	CARTON (qty)	UPC
S0115-FS07	1/4"	0.31"	0.46"	0.87"	1.48"	1.60"	0.60"	1,000	0.09	POLYBAG	1	25	400	791506028994
S0115-FS08	5/16"	0.38"	0.52"	1.02"	1.71"	1.83"	0.71"	1,300	0.15	POLYBAG	1	25	200	791506029007
S0115-FS10	3/8"	0.44"	0.65"	1.24"	2.12"	2.27"	0.91"	1,500	0.27	POLYBAG	1	10	120	791506029014
S0115-FS12	7/16"	0.50"	0.75"	1.43"	2.37"	2.61"	1.00"	2,000	0.38	POLYBAG	1	10	100	791506029021
S0115-FS13	1/2"	0.63"	0.79"	1.58"	2.74"	2.90"	1.18"	3,000	0.61	POLYBAG	1	5	60	791506029038
S0115-FS16	5/8"	0.75"	1.05"	1.94"	3.32"	3.61"	1.45"	4,000	1.15	POLYBAG	1	1	30	791506029045
S0115-FS20	3/4"	0.88"	1.20"	2.40"	3.94"	4.36"	1.72"	6,000	1.95	POLYBAG	1	1	15	791506029052
S0115-FS22	7/8"	1.00"	1.45"	2.88"	4.50"	5.32"	1.95"	8,000	3.02	POLYBAG	1	1	10	791506029069
S0115-FS25	1"	1.13"	1.67"	3.20"	5.21"	5.78"	2.20"	10,000	4.26	POLYBAG	1	1	8	791506029076

NOTE:

**I/A/W FED. SPECIFICATION RR-C-271, TYPE IVB, CLASS 2, (EXCEPT 316 STAINLESS STEEL). MEETS THE REQUIREMENTS OF: MIL-DTL-32655.
MEETS ASME B30.26-2010 SECTION 26-0. MARKED TO THE NEAREST FRACTIONAL TON.
ALL DIMENSIONS ARE NOMINAL (+/- 3%) AND ARE SUBJECT TO CHANGE WITHOUT NOTICE.**