

SPRING CLIP - KEY LOCK

316 STAINLESS STEEL




Import



Wire
Formed



Load
Rated



| ITEM | A | B | C | D | X (height) | Y (length) | Z (width) | WLL (lb) | WT (lb) | PACKAGING TYPE | EACH (qty) | INNER (qty) | CARTON (qty) | UPC |
|------------|-------|-------|-------|-------|---------------|---------------|--------------|-------------|------------|-------------------|---------------|----------------|-----------------|--------------|
| S0120-K050 | 3/16" | 0.31" | 0.29" | 0.20" | 0.98" | 2.00" | 0.19" | 200 | 0.04 | POLYBAG | 1 | 10 | 1000 | 791506030928 |
| S0120-K060 | 1/4" | 0.35" | 0.37" | 0.21" | 1.20" | 2.38" | 0.23" | 250 | 0.07 | POLYBAG | 1 | 10 | 500 | 791506030935 |
| S0120-K070 | 9/32" | 0.46" | 0.40" | 0.33" | 1.35" | 2.88" | 0.27" | 300 | 0.10 | POLYBAG | 1 | 10 | 250 | 791506030942 |
| S0120-K080 | 5/16" | 0.44" | 0.43" | 0.33" | 1.53" | 3.25" | 0.31" | 400 | 0.16 | POLYBAG | 1 | 5 | 200 | 791506030959 |
| S0120-K100 | 3/8" | 0.55" | 0.60" | 0.40" | 1.94" | 4.00" | 0.38" | 600 | 0.30 | POLYBAG | 1 | 5 | 100 | 791506030966 |
| S0120-K120 | 7/16" | 0.69" | 0.70" | 0.57" | 2.19" | 4.75" | 0.43" | 800 | 0.43 | POLYBAG | 1 | 1 | 50 | 791506030973 |
| S0120-K160 | 1/2" | 0.87" | 1.18" | 0.75" | 3.17" | 6.38" | 0.52" | 1,000 | 0.78 | POLYBAG | 1 | 1 | 25 | 791506030980 |

NOTE:

KEY LOCK MECHANISM. EACH CLIP IS PROOF TESTED AND STAMPED WITH THE BREAK LOAD. CLIPS S0120-K050 - S0120-K070 ARE MARKED IN KILOGRAMS (CONVERSION: KGX2.2=LB), WHILE S0120-K080 - S0120-K160 ARE MARKED IN KILONEWTONS (CONVERSION: KN X 224.8 = LB). ALL DIMENSIONS ARE NOMINAL (+/- 3%) AND ARE SUBJECT TO CHANGE WITHOUT NOTICE.