

# FED. SPEC. EYE AND EYE SWIVEL

## 316 STAINLESS STEEL



Import




Drop Forged



Suncor Exclusive



MIL-SPEC



ITEM	A	B	C	D	E	F	X (height)	Y (length)	Z (width)	WLL (lb)	WT (lb)	PACKAGING TYPE	EACH (qty)	INNER (qty)	CARTON (qty)	UPC
S0128-FS07	1/4"	0.75"	1.06"	0.80"	0.31"	2.92"	1.25"	3.37"	0.60"	900	0.17	POLYBAG	1	5	200	791506032588
S0128-FS08*	5/16"	1.25"	1.50"	1.17"	0.38"	4.29"	2.00"	5.00"	0.94"	1,500	0.67	POLYBAG	1	1	50	791506032595
S0128-FS10	3/8"	1.25"	1.50"	1.06"	0.50"	4.29"	2.00"	5.00"	0.94"	2,600	0.70	POLYBAG	1	1	25	791506032601
S0128-FS13	1/2"	1.50"	2.00"	1.45"	0.63"	5.42"	2.50"	6.50"	1.17"	4,400	1.39	POLYBAG	1	1	25	791506032618
S0128-FS16	5/8"	1.75"	2.38"	1.73"	0.75"	6.55"	3.00"	7.73"	1.41"	6,000	2.42	POLYBAG	1	1	15	791506032625

**NOTE:**

**I/A/W FED. SPECIFICATION RR-C-271F TYPE VII, CLASS 2 (EXCEPT 316 STAINLESS STEEL). MEETS THE REQUIREMENTS OF: MIL-DTL-32655 (\*EXCLUDING S0128-FS08). SWIVELS ARE POSITIONING DEVICES AND ARE NOT INTENDED TO ROTATE UNDER LOAD. MARKED WITH SIZE AND WORKING LOAD LIMIT ALL DIMENSIONS ARE NOMINAL (+/- 3%) AND ARE SUBJECT TO CHANGE WITHOUT NOTICE.**